NAVAC

Empowering you to work smarter

NH5S
Charging Hose Set w/o Ball Valve



NH5R
NH5B
NH5Y
NH5L
Individual Charging Hose w/o Ball Valve



NH5L

A2L Compatible

NH5SC
Charging Hose Set with Ball Valve



NH5CR
NH5CB
NH5CY
Individual Charging Hose with Ball Valve



1/4" Color Hoses, 5 Ft Long

Main Features for All Models


- Suitable for R-410A, R-134a, R-22 and other refrigerants
- 1/4" SAE fittings with 45° bend on one end
- Leak-proof eight-sided crimp
- 800 psi working pressure, 4000 psi burst pressure
- Universal, replaceable gasket
- Adjustable depressor

Ball Valve Models

- Ball valve for reduced refrigerant loss
- Metal valve handle

NH5L

- Reverse threaded for A2L



The valve core depressor can be adjusted up or down to optimize its access to valve core. Use a valve core depressor adjustor to turn the depressor. To lower, turn clockwise; to raise, turn counterclockwise.

Model		NH5S	NH5R	NH5B	NH5Y	NH5L	NH5SC	NH5CR	NH5CB	NH5CY
Color		Red, Yellow, Blue	Red	Blue	Yellow	Orange	Red, Yellow, Blue	Red	Blue	Yellow
Quantity	pc	3	1	1	1	1	3	1	1	1
Ball Valve		Without ball valve					With ball valve			
Pressure Scale	psi	0~800 psi								
Length	ft	5								
Connector	in	1/4" - 1/4"								

1-YEAR WARRANTY