





# **Fastest in Its Class**

#### Fastest in Direct Vapor for R410A, R22

• UL verified recovery rate, best performance in its class

# Twin Cylinder with 2-Row Oversized Condenser

Fast recovery

#### **Brushless DC Motor**

• Light and more efficient

## Oil-Free Compressor

• Suitable for all commonly used refrigerants

#### Large Backlit Display

- Easy-to-read large LCD display
- Backlit for clarity

## **Purge Function**

• Prevent mixing of various refrigerants

Model		NRDD				
Refrigerant Type		Category III: R-12, R-134a, R-401C, R-500, R-1234YF Category IV: R-22, R-401A, R-401B, R-402B, R-407C, R-407D, R-408A, R-409A, R-411A, R-411B, R-412A, R-502, R-509 Category V: R-32, R-402A, R-404A, R-407A, R-407B, R-410A, R-507				
Power Supply	V/Hz	115V/60Hz				
Motor	HP	1				
Max Current Draw	Α	12				
Compressor		Oil-less, Air-cooled, Piston style				
Automatic Safety Shut-Off		558 psi/38.5 bar				
UL Verified Recovery Rate VERIFIED			R-410A	R-22	R-134a	
	lbs/min	Direct Vapor	0.75 (0.34) 🍅	0.64 (0.29)	0.57 (0.26)	🛍 Industry Fastest
	(kg / min)	Direct Liquid	14.44 (6.55)	11.11 (5.04)	7.85 (3.56)	
		Push/Pull Liquid	18.41 (8.35)	17.04 (7.73)	12.81 (5.81)	
Dimension	in	14.5×9.9×11.7				
Weight	lbs	24.3				