

We Know Water.

BI-LEVEL VERSACOOLER® II • PG8ACSL • PGACSL

Suggested Specification

Model PG8ACSL shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model PGACSL is a non-refrigerated drinking fountain and delivers ambient water. Shall include four push pads. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Cabinet finish shall be brushed stainless steel or greystone on galvanized steel. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.

		PG8ACSL	PGACSL
Features:		Universal design allows universal installation	
		Built-in 100 micron strainer stops particles before they enter the waterway	
		Waterways are Lead-Free in materials & construction	
		Flexible and one-piece water saver bubbler	
		Stainless steel top and heavy duty galvanized steel frame	
		Four push pads per side	
		External stream height adjustment	
		Mechanical activation	
Filtration:	Option to add Versafilter Filtration System		
Power:	115 Volts, 60 Hz		
Activation By:	Manual Activation		
Mounting Type:	Wall Mounted		
Chilling Option:		8.0 gph	Non-Refrigerated
Installation Location:	Indoor		



Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- · Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation

Finishes

- Standard cabinet finish: Greystone powder coated paint on galvanized steel
- Optional finishes: Sandstone powder coated paint; Stainless steel (at additional cost)

Options

- Push handle glass fillers (029603-004)
- One piece chrome plated brass bubbler (036700-001)
- Cane apron (035174-001)
- VersaFilter

Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.
- These waters coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed.



*Industry standard rating condition 80°F inlet water temperature

Specifications subject to change without notice

OASIS® BI-LEVEL VERSACOOLER® II MODELS

