

VERSAFILLER® CONTACTLESS RETROFIT BOTTLE FILLING STATION KIT, NON-REFRIGERATED

MODEL PWEBF

Suggested Specification

When retrofitted to either the PG8AC or P8AM, the PWEBF bottle filler shall include contactless activation and laminar flow. VersaFiller alcove and cabinet shall be stainless steel. Key VersaFiller components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Unit shall include filter monitor and bottle counter. When retrofitted to either the PG8AC or P8AM the VersaFiller models satisfy ANSI A117.1 and ADA requirements when properly installed. Units also meet guidelines for children's accessibility providing the floor to orifice height is 30 inches and proper clear floor space is provided for frontal approach. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 377

- Built-in 100 micron strainer stops particles before they enter the waterway
- Waterways are lead-free in materials & construction
- · Heavy duty galvanized steel frame
- Contactless activation bottle filler with programmable auto shut off

Features:

Approx. Net

Installation

Location:

Weight

- Access filtration through the top of the bottle filler for clean and easy replacement of filters with Tilt 'N Tether
- Ample space within the bottle filler cabinet to add filtration, including all OASIS filters
- · Built-in filter monitor and bottle counter
- Logos permanently formed into the alcove and stainless steel wrapper

19 lbs

Indoor

- · LED lighted alcove
- Surface mount frame assembly

Filtration:	Utilizes existing filtration if applicable. Option to add filtration to top of bottle filler
Power:	115 Volts, 60 Hz
Activation By:	Contactless Sensor on Bottle Filler
Mounting Type:	Wall Mounted
Chilling Option:	Utilizes existing refrigeration system if applicable
Full Load Amps	0.2 amps
Rated Watts	11

MODEL: QTY: PROJECT: CONTACT: NOTES: APPROVAL: DATE:



Ships in one box.

Installation

- The PWEBF VersaFiller is designed to retrofit existing OASIS PG8AC and P8AM pressure cooler models. Units with optional glass fillers must have the glass filler disconnected and removed.
- Prior to rough-in consult with local, state, and federal codes for proper mounting height.
- Shipped with complete instructions and wall mounting brackets.

Finishes

· Standard cabinet finish: Stainless steel

Limited 1-Year Warranty

(Continental limits of the United States and Canada)
One year on bottle fillers and electrical components. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These waters coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



WARNING:

Cancer and Reproductive Harm www.P65Warnings.ca.gov









Specifications subject to change without notice



VERSAFILLER® CONTACTLESS RETROFIT BOTTLE FILLING STATION KIT, NON-REFRIGERATED

MODEL PWEBF

Accessories



Elkay® Adapter Gasket OASIS Item #041533-001

Elkay Adapter Gasket is necessary to complete installation if retroftting to an Elkay® fountain



OASIS VersaFilter III Universal Retrofit Kit

OASIS Item #041253-001

Add filtration to your unit - retrofit into all OASIS fountains and bottle fillers. Certified to NSF/ANSI 42, 53 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons.



OASIS Total PFAS Universal Retrofit Kit

OASIS Item #041253-005

Add filtration to your unit - retrofit into all OASIS fountains and bottle fillers. Certified to NSF/ANSI 42, 53 and 401 for chlorine, taste, odor, particulate class 1, lead, cysts, Total PFAS, and microplastics reduction to 1,100 gallons.



OASIS Pharmaceutical Universal Retrofit Kit

OASIS Item #041253-006

Add filtration to your unit - retrofit into all OASIS fountains and bottle fillers. Certified to NSF/ANSI 42, 53 and 401 for chlorine, taste, odor, particulate class 1, lead, cysts, Atenolol, Bisphenol A, Carbamazepine, DEET (diethyltoluamide), Estrone, Ibuprofen, Meprobamate, Metolachlor, Naproxen, Nonyl phenol, Phenytoin and Trimethoprim, and microplastics reduction to 725 gallons.



View all filters and accessories



VERSAFILLER® CONTACTLESS RETROFIT BOTTLE FILLING STATION KIT, NON-REFRIGERATED

MODEL PWEBF

