

The simple disk skimmer tackles heavy oil loads.

FEATURES:

- Handles heavy oil loads from coolant and washwater applications
- Intermittent-duty motor (refer to Smart Disk Skimmer for continuous-duty motor and coolant-free output)
- Warranty (lifetime on wipers and 90-day on disks)
- Up to 5 gallons per hour oil removal capacity
- ½" x 12" (13 x 300mm) sump access needed (for 12" model)
- Maximum temperatures:
80°F (27°C) for high-impact disks for coolant
212°F (100C) for high-temperature disks for wash water
- Recommended accessory shown below



To determine the reach required, measure the distance from the mounting point to the lowest operating fluid level.

Model	Part Number	Description
L Skimmer	LH300	Simple Disk Skimmer, 12" high-impact disk, reach of 4.5"
	LH460	Simple Disk Skimmer, 18" high-impact disk, reach of 7.0"
	LH610	Simple Disk Skimmer, 24" high-impact disk, reach of 9.5"
	LW300	Simple Disk Skimmer, 12" high-temperature disk, reach of 4.5"
	LW460	Simple Disk Skimmer, 18" high-temperature disk, reach of 7.0"
	LW610	Simple Disk Skimmer, 24" high-temperature disk, reach of 9.5"

Timer	XETIMER	External timer for mechanical skimmers 24 hour, 3 setting
LW Series (Replacement disks, wipers, and collars)	DISK-H300	12" (300mm) Disk, 1/4" (6.35mm) thick, temps to 90°F (32°C)
	DISK-H460	18" (460mm) Disk, 1/4" (6.35mm) thick, temps to 90°F (32°C)
	DISK-H610	24" (610mm) Disk, 1/4" (6.35mm) thick, temps to 90°F (32°C)
	LXWIP	Wiper set for all Zebra model disk skimmers
	LXCOL-A	Aluminum collar for disk skimmers, 5/16" (7.9mm) opening

Motor Number	Models Number	Volts	Hz	LRA	RPM	Watts	HP	Fan
MG07A1	LH300, LH460, LW300, LW460	115	60	0.43	7	49	0.065	Y
MG02A1	LH610, LH610E, LW610, LW610E	115	60	0.43	2	49	0.065	Y
MG06E1	LH300E, LH460E, LW300E, LW300E, LW460E	220	50	0.22	6	48	0.064	Y

Models with "E" at the end are our 220v units.



Zebra Skimmers Corporation

27000 Richmond Road #1 | Solon, OH 44139 | Toll Free: 888.249.4855 | Fax: 440-349-1211
sales@zebraskimmers.com | www.zebraskimmers.com