

Sumpster™:

SPECIFICTIONS & PARTS

Zebra Z17 Coalescer

Z17 Series - Technical Specifications

Barrel: 15 gallons (57 liters), 22" (56cm) high, 17" (43cm) diameter Pump, Standard: 3 gpm (3.8 lpm), w/ max 4' lift, 4" (10cm) high, 3" (7.6cm) wide,

4" (10cm) long

Standard Electrical: 110v, 60Hz standard

Flowrate: Z17 ships with a blue .125 flow restrictor installed. Two additional flow

restrictors (green .25 and orange .5) ship with the unit to facilitate

balancing the system to shop conditions.

Hammerhead[™]: 4.5" (114mm) x 3.25" (82mm) x 1.75" (45mm) w/1' (304mm) oil

intake hose (max length), 1 gpm (3.78 lpm) max flow rating

5" (127mm) x 4 1/4" (108mm) x 4 5/8" (117mm), 3gpm (11 lpm)

max flow rating

Floating Sumpster™: 11" (279mm) x12" (305mm) x 6" (152mm), 3gpm (11 lpm) max

flow rating

Intake Hose: 48" (1.2m) long, 0.5" (12mm) ID (customization available to 15'

(4.5m) (max)


Discharge Hose: 48" (1.2m) long, 1.25" (32mm) ID (customization available to 8'


(2.4m) (max)

Maximum Temp: 100° F (38° C)

Shipping Weight: 28-31 pounds (12 to 14 kg), dimensional weight, dependent upon

model






Z17 Series - Replacement Parts & Accessories

SK02D12F Zebra Hammerhead floating skimmer attachment SK10A7 Zebra Sumpster free-standing skimmer attachment SK10B2.3S Zebra Floating Sumpster skimmer attachment


FXDD15 Drum dolly; Polyethlene, 16 3/8" 41.4cm) dia., (4) 3" (76mm) dia. casters,

600 lb. (272kg) capacity

FXCM004 Coalescing media (1/2 cubic foot)
SK95 Clear spiral wound, 1.25" ID, 1' section
SK97 Clear braided hose 1/2" ID, 1' section
SK99 Black flexible hose, 1/2" ID, 1' section



B. SUMPSTER 5 x 4.25 x 4.625"



C. FLOATING SUMPSTER 13 x 11 x 7"