

DS-K1T501SF

Video Access Control Terminal

DS-K1T501SF is a kind of video access control terminal, which is equipped with HD camera (2 MP/1080p) and fingerprint recognition module (supporting 1:1 mode and 1:N mode). It supports multiple advanced technologies including fingerprint recognition, face detection, smart card recognition, two-way audio, remote live view, picture capture, video recording through NVR, and so on. It also supports multiple authentications including card, fingerprint, card and fingerprint, etc.



Available Models

DS-K1T501SF

* *Recommended Fingerprint Recorder Model to Use Cooperatively: DS-K1F820-F*

Features

- Brushed metal surface
- Communication via TCP/IP and Wi-Fi
- Supports EHome protocol for public network communication
- Face detection and picture capturing function implemented by built-in camera (1080P/2MP and IR light, optional)
- Built-in Micro SD card slot; Supports inserting Micro SD card (Max. 128G) and saving captured pictures and recorded videos to the memory card
- QR code authentication; Generates QR code via iVMS-4200 client software or other systems
- Two way-audio
- Opens door remotely via iVMS-4200 client software or other systems
- Max. 50,000 cards No., Max. 200,000 access control event records and Max. 5000 fingerprints storage
- Supports Mifare card reading
- Multiple authentication modes: QR code, card, fingerprint, card + fingerprint, card + password, fingerprint + password, card + fingerprint + password, and so on
- Working as a card reader, and supports Wiegand interface and RS-485 interface for accessing the controller
- RS-485 communication for connecting external card reader
- Connects the external secure door control unit via RS-485 to avoid the door opening when the terminal is destroyed
- Protection level: IP65



- Voice prompt for the results of authentication by card
- Tampering detection, unlocking overtime alarm, invalid card swiping over times alarm, duress card alarm, and so on

Specifications

Model	DS-K1T501SF
Processor	32 bit high-performance processor
Camera	2MP/1080P, IR light
Audio	Audio input: built-in micro phone (sensitivity: -25 ± 3 DB) Audio output: built-in loudspeaker (1 W)
Card capability	50,000
Record capability	200,000
Fingerprint module	Optical fingerprint recognition module
Fingerprint capability	5000
1:N fingerprint recognition speed	≤ 1.5 s
False acceptance rate (RAR)	≤ 0.001 %
False recognition rate (FRR)	≤ 0.01 %
Card reading mode	Mifare card
Induction distance	≥ 2 cm
Communication mode	Terminal mode: TCP/IP and RS-485 Card reader mode: Wiegand (26/34) and RS-485
Input interface	Doorbell Button $\times 1$, Door Contact $\times 1$, Alarm Input $\times 2$, Tamper Alarm $\times 1$, Exit Button $\times 1$
Output interface	Lock Relay $\times 1$, Alarm Output (Doorbell) $\times 1$
Video storage	Record and save video through NVR or Micro SD card
Micro SD card	Max. 128 G
Protection level	IP65
Power supply	12 VDC/1 A
Working current	Max. 600 mA
Working temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Working humidity	10% to 90% (No condensing)
Mounting	Wall mounting
Dimension	218 mm \times 78 mm \times 41 mm (8.58" \times 3.07" \times 1.61")

* Exposing the equipment to direct sun light, low ventilation or heat source such as heater or radiator is forbidden (ignorance can cause fire danger).

* For device with fingerprint module, we suggest that do not install the device outdoors.

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com